

STARTING MACHINE

- 1) CONNECT EXTENSION POWER CORD TO PIGTAIL CORD
- 2) PLUG EXTENSION CORD INTO A GROUNDED OUTLET
- 3) DO NOT OPERATE MACHINE WITH THE USE OF ADDITIONAL EXTENSION CORDS. THIS WAY MACHINE IS PROPERLY GROUNDED

SQUEEGEE WET VACUUMING

- 1) HINGE OPEN RECOVERY TANK AND REMOVE VACUUM BAG FROM RECOVERY TANK
- 2) LOWER SQUEEGEE TO FLOOR, LIGHTLY KICK PEDAL FORWARD TO RELEASE FROM TRANSPORT
- 3) TURN ON SWITCH AND BEGIN VACUUMING. SQUEEGEE VACUUMS UP WATER IN BOTH FORWARD AND REVERSE
- 4) TO RAISE SQUEEGEE, STEP DOWNWARD ON THE PEDAL UNTIL PEDAL ENGAGES IN TRANSPORT POSITION

ACCESSORY TOOL WET VACUUMING

- 1) HINGE OPEN RECOVERY TANK AND REMOVE VACUUM BAG FROM RECOVERY TANK
- 2) ATTACH APPROPRIATE TOOL TO VACUUM HOSE AND ACTIVATE POWER SWITCH. OPERATE TOOL AS NORMAL

DRAINING RECOVERY TANK

- 1) PUSH MACHINE TO NEAREST FLOOR DRAIN
- 2) REMOVE DRAIN HOSE FROM HOLDER AND TWIST OFF KNOB AND DRAIN. RAISE HOSE TO STOP FLOW OF WATER
- 3) WHEN RECOVERY TANK IS EMPTY, OPEN LID AND RINSE TANK WITH CLEAN WATER TO PREVENT ODOR BUILD UP
- 4) REPLACE DRAIN HOSE KNOB AND RETURN TO HOLDER

DRY VACUUMING

- 1) PLACE A CLOTH FILTER BAG INTO RECOVERY TANK AND MAKE SURE THAT EDGE SEALS PROPERLY AGAINST RIM OF TANK
- 2) CLOSE LID AND FASTEN LATCHES
- 3) ACTIVATE SWITCH AND OPERATE ACCESSORY TOOLS AS NORMAL
- 4) CHECK BAG PERIODICALLY FOR FULLNESS. EMPTY BAG AT 3/4 FULL FOR BEST SUCTION PERFORMANCE
- 5) NEVER USE PAPER BAG WITHOUT CLOTH FILTER BAG IN PLACE. DO NOT REUSE PAPER BAGS--ALWAYS DISPOSE. ALWAYS MAKE SURE THAT BAG IS IN PLACE BEFORE DRY VACUUMING. DRY VACUUMING WITHOUT BAG IN PLACE WILL DAMAGE VACUUM MOTOR. THIS DAMAGE IS NOT COVERED BY WARRANTY